

ITA 41

STEEL STRAPPING TOOL > PNEUMATIC

Pneumatic Steel Strapping Tool with Seal for 19mm / 25mm / 32mm Steel Strap

ITA 41 is the combined pneumatic strapping tool for 19mm / 25mm / 32mm steel straps.

The tool is equipped with 3 operating buttons, to allow a Manual tension of Your steel strap.

ITA 41 is available in two motor versions (9000 N and 15000 N) to provide the most suitable and adjustable tension for Your application.

Easy to be used, ITA 41 is already equipped with its suspension hook to grant a lighter operation mode and to arrange a perfect double notch seal joint.

Powerful, quick and strong, ITA 41 is manufactured to be durable and with very low maintenance required



FEATURES

3 Operating Buttons
Strong and Reliable
Easy to be used
Low Maintenance Required
Powerful and Quick

BENEFITS

Double Notch Seal Joint
Manual Tension
Robust and durable
For a wide range of steel Straps
Suspension hook already equipped

TECHNICAL SPECIFICATION

| | |
|-------------------|--------------------|
| Dimensions | 430 x 260 x 310 mm |
| Weight | 10,3 Kg |

STRAP

| | |
|------------------|---|
| Type | Steel Strap - regular & high tensile |
| Width | 19mm / 25mm / 32mm |
| Thickness | 0,6mm - 1,0mm (Regular duty) 0,63mm - 0,8mm (High Tensile) |

POWER SUPPLY

| | |
|------------------------|---------------------------|
| Pressure Range | 5.5 - 7 bar (78 - 99 psi) |
| Air Consumption | 12 L/s - 25 cuft/min |

PERFORMANCE

| | |
|---------------------------|---|
| Max. tension force | 9000N - 15000N (6 bar - 87 psi) |
| Tensioning Speed | 3,8 mt/min @9000N 5,2 mt/min @15000N |
| Sealing | Seal Double Notch |
| Joint Strenght | 75% of breaking strenght* |

* variable according to strap type

MODEL

| CODE | DESCRIPTION |
|---------|------------------------------|
| T411943 | ITA 41 - 19mm Steel - 9000N |
| T412543 | ITA 41 - 25mm Steel - 15000N |
| T413243 | ITA 41 - 32mm Steel - 15000N |